

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/110866 A1

(51) International Patent Classification⁷: **B65B 25/00**

(74) Agent: DALL'OLIO, Giancarlo, Interbrevetti S.r.l., Via delle Armi 1, I-40137 Bologna (IT).

(21) International Application Number:
PCT/IB2004/002000

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 16 June 2004 (16.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BO2003A000371 18 June 2003 (18.06.2003) IT

(71) Applicant (for all designated States except US):
SICHERA S.R.L. [IT/IT]; Via dei Carpentieri, 3, I-40050 Castello d'Argile (IT).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW). Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM). European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR). OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SICHERA, Gianni [IT/IT]; Via Provinciale Cento, 16/B, I-40066 Pieve di Cento (IT). SICHERA, Massimiliano [IT/IT]; Via Renazzo, 63, I-44045 Renazzo di Cento (IT).

[Continued on next page]

(54) Title: A METHOD FOR PACKAGING CD, DVD AND THE LIKE



(57) Abstract: According to a method for packaging CDs, DVDs and similar digital record carriers in a corresponding foldable package (10), including a blank (11) and one or more trays (12) glued to corresponding blank sections (13), the discs (1) are first introduced into housings (15) made in the trays (12) before the trays are applied to the blank sections (13). After a suitable glue has been applied to the trays (12), containing the discs (1), the trays (12) are set in contact with the sections (13), and then the so obtained package (10) is conveyed toward further work stations. The glue can be applied to the trays (12) also before placing the discs (1), and anyway, in any moment before the trays (12) are applied to the blank sections (13).



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

- 1 -

A METHOD FOR PACKAGING CD, DVD AND THE LIKEBACKGROUND OF THE INVENTION

The present invention relates to procedures and
5 apparatuses for packaging disc-shaped digital record
carrier for recording information in digital form, known
as CDs (Compact Discs) or DVDs (Digital Versatile Discs).

In particular, the invention relates to a new method for
packaging the above mentioned discs into book-like
10 containers, including one or more trays, each of which is
aimed at receiving one disc.

DESCRIPTION OF THE PRIOR ART

Discs containing information in digital form, and mainly
15 those containing audio data (CD) or audio-video (DVD),
are often packaged in foldable containers, aimed at
containing one or more discs.

These containers are made from a blank, usually formed
by a printed cardboard, divided in sections, which can be
20 folded one over another toward the inside of the
container.

The section folding order depends on the width of the
section connecting areas, which are to form the sides of
the container.

25 The width of one connecting area must be determined
taking into consideration the whole thickness of the
sections already folded one over another.

The inner faces of some, or of all, above mentioned
sections have, associated thereto, trays made in plastic

- 2 -

material, usually transparent, shaped in such a way, as to contain and removably lock a corresponding disc.

The trays are fastened to the corresponding sections by applying, by suitable devices, a layer of glue onto the
5 surface of the tray aimed at matching with the section of the blank.

Then, the trays are put on the sections by suitable manipulating means.

The so obtained container is then conveyed to a filling
10 station, in which other manipulating means arrange the discs in the respective positions, after locating above their seats.

A drawback, which is often reported in the automatic machines performing the above operations, derives from
15 the fact that, although each tray is positioned on the corresponding section of the blank with extreme precision, the glue which must mutually fasten the two elements, does not act immediately, and consequently, the position of a tray with respect to the container can be
20 changed during transport of the container after gluing.

These possible position changes, even if small, can put at risk the subsequent positioning of the disc in the relative seat and interrupt, or at least delay the discs packaging operations.

25 Known packaging machines have tried to solve the above problem by introducing devices for centering the disc on the relative tray, before the disc is positioned on the tray.

These devices act on each disc, detecting the exact
30 position of the corresponding tray, previously glued to the relative blank section, by suitable sensor means.

- 3 -

The position of the disc manipulating means can be corrected, in order to bring it in axis with the seat. This increases considerably the apparatus complexity, and consequently, its cost.

- 5 The discs must be centered one by one, therefore the above described apparatuses cannot operate on more discs at the same time.

Since it is not possible to define a fixed flush-reference point in the packaging machine, the size
10 change-over, with containers having different number of trays, or with trays folded in a different order, becomes extremely complicated and it can create devices calibration problems, as well as increase the machine downtimes.

15

SUMMARY OF THE INVENTION

The object of the present invention is to propose a method for packaging disc-shaped digital record carriers for recording information, such as CDs and DVDs, in trays
20 associated to suitable containers, according to which method the discs are introduced into said trays independently from undesired movements of the trays with respect to the blanks, after the gluing operation.

Another object of the present invention is to propose a
25 method which allows a secure positioning of a plurality of record carriers on the trays, arranged parallel, independently from undesired movements of the trays.

The above mentioned objects are achieved by means of a method for packaging disc-shaped digital record carriers
30 in a corresponding folding package, said package including a blank and a tray fastened to a corresponding

- 4 -

section of said blank, said method being characterized in that it includes a cyclical repetition of the following operation steps:

- Feeding a tray along a first path of a line for
5 packaging said discs, said tray having in its first surface a housing for receiving a disc;
 - Feeding a disc along a second path of said packaging line, converging toward said first path at a convergence point, and moving said disc until it is aligned with the
10 housing of the tray;
 - introducing said disc in said housing;
 - feeding said blank along a third path of said packaging line, said third path intersecting said first path at an assembling station of said package, downstream
15 of the above mentioned convergence point between the first path and the second path;
 - placing said tray and said section in mutual alignment, after introduction of the disc into said tray;
 - assembling, in said assembling station, said tray to
20 an inner surface of said section, with interposition of a layer of gluing material, to fasten said tray to said section and to obtain said package;
 - conveying said package toward a station, where it is folded to the closed conformation.
- 25 According to a different embodiment of the invention, the method is for packaging disc-shaped digital record carriers in a corresponding folding package, with said package including a blank and a predetermined number of trays, each of said tray being fastened to a
30 corresponding section of said blank, said method being

- 5 -

characterized in that it includes a cyclical repetition of the following operation steps:

- feeding a predetermined number of trays, set side by side, along a first path of a line for packaging said
5 discs, each of said tray having a housing in a first surface for receiving a disc;
- feeding as many discs as there are trays on the first path of the packaging line, along a second path of said packaging line, converging toward said first path at
10 a convergence point, and placing each disc in alignment with a housing of a corresponding tray;
- introducing each of said discs in a corresponding housing;
- feeding said blank along a third path of said
15 packaging line, said third path intersecting said first path at an assembling station of said package, downstream of the above mentioned convergence point between the first path and the second path;
- setting each of said trays in alignment with a
20 corresponding section, after the introduction of the discs into said trays;
- assembling, in said assembling station, each of said trays to the inner surface of the corresponding sections, with interposition of a layer of gluing material, in
25 order to fasten each tray to a corresponding section and to obtain said package;
- conveying said package toward a station, where it is folded to the closed conformation.

Preferred features of the invention are defined in the
30 dependent claims.

- 6 -

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in more detail with reference to particular, non-limiting embodiments and
5 with reference to the accompanying drawings, in which:

- Figures 1A, 1B, 1C, 1D are schematic top views of some containers of the type to which the invention refers, which differ one from another by the number of disc seats;
- 10- Figure 2 is a schematic sequence of packaging of discs according to the invention, in a container of the type shown in Figure 1A;
- Figure 3 is a schematic sequence of packaging of discs according to the invention, in a container of the
15 type shown in Figure 1D.

BEST MODES OF CARRYING OUT THE INVENTION

With reference to the Figures 1A, 1D, 1B, 1C, the reference numerals 10, 110, 120, 130 indicate
20 respectively an equal number of foldable packages in open configuration.

The packages are aimed at containing one or more CDs, DVDs or similar record carriers for storing information in digital form.

25 The difference between the packages 10, 110, 120, 130 lies in the number of discs they can contain.

In particular, there are shown packages for 1, 2, 3 and 4 discs, respectively, but generally these packages can contain any number of record carriers.

- 7 -

With particular reference to Figures 1A and 2, taken as an example, the package 10 includes a blank 11, formed by three sections 16, 13, 17, arranged one beside another.

The sections are separated one from another in known way,
5 by connection areas 18, 19, whose width is different in function of the folding order of the package 10.

The package 10 includes also a tray 12, made in a first surface 14 of a housing 15 for receiving a corresponding disc 1.

10 The tray is to be assembled with the blank 11 in correspondence to the inner surface 13a of the section 13, in ways and times which will be explained in detail in the following description of the present method.

Likewise, ways and times for fastening the tray 12 to
15 the section 13, by gluing, will be explained better later on.

The remaining sections 16, 17 of the blank 11 contain usually graphics and writings related to the contents of the packaged disc, and are aimed at being folded on the
20 section 13.

All the above mentioned sections 13, 16, 17 can be provided with pockets for containing, e.g. informative sheets, or even other discs.

The packaging method according to the present invention
25 will be described in the following, as a mere, non limiting example, with reference to the embodiments related to the packages 10, 110 containing one and four discs, respectively.

In the first case, a sequence of packaging and
30 contemporary assembling of the packages is performed cyclically on a line for packaging discs 1 to the

- 8 -

packages 10, according to what is reported in detail in the following.

First of all, a tray 12 having a relative housing 15 is fed along a first path A of the packaging line.

- 5 Suitable and known manipulating means feed a disc 1 along a second path B, converging with the first path A to a filling station, not shown, until the disc is aligned with the housing 15 and above it.

- 10 Then, the disc 1 is introduced into the housing 15, in its definite position, and the tray 12 continues its run along the first path A.

A blank 11, obtained as described previously, is fed along a third path C of the packaging line.

- 15 The third path C crosses the first path A, remaining below the latter, at an assembling station, not shown, situated downstream of the filling station.

The tray 12 is aligned with the corresponding section 13 in the assembling station.

- 20 In the meantime, known applying means apply a layer of gluing material to the lower surface 24 of the tray 12.

Actually, the exact moment of glue application is not critical for the present invention.

- 25 In fact, it is all the same whether the glue is applied before the tray 12 is filled with the disc 1, or after, even in the assembling station.

It is only necessary that the glue is applied before the next step of the method is performed, as it will be described later on.

- 9 -

Moreover, the layer of the gluing material can be applied to the inner surface 13a of the section 13, or both to the latter and to the second surface 24 of the tray 12.

Anyway, the first described way of application is
5 generally easier.

During the subsequent step of the method, the tray 12 is fastened to the inner surface 13a of the section 13, to obtain gluing of the tray 12 and consequently, to complete the package 10.

10 At this point, the package is conveyed to a subsequent folding station, and possible further stations of application of plastic film, according to conventional methods.

As far as the packages 10 containing two or more discs 1
15 are concerned, the main steps are briefly described with reference to the above mentioned package 110, containing four discs (Figures 1D and 3).

In this case, for each packaging cycle, four trays 112 are fed parallel along the first path A; however,
20 feeding the trays in a series one after another, is also possible.

The trays 112 are preferably maintained one beside another, to control their position in a better way.

The housings 115 of the trays 112 are then filled at the
25 same time with the corresponding discs 1, fed on the second path B by the multiple manipulating means, likewise commonly used in the conventional packaging lines.

In the meantime, a blank 111 is fed along the third path
30 C. The blank 111 includes four sections 113 aimed at

- 10 -

receiving the corresponding trays 112, and further sections 116, 117, which are not to receive trays.

The presence of these last mentioned sections is not necessary and depends on the configuration of the package
5 110.

The sections 113 are separated one from another by connection areas, whose width depends on the folding order of the package 110.

The trays 112 are then laterally spaced apart (Figure 3),
10 in relation to the width of different connection areas, and then they are brought in line with the relative sections 113 in the assembly station.

Also in this case, a gluing material is applied to the second surface of the trays 113, turned toward the inner
15 surfaces 113a of the sections 113, before their assembling.

In the subsequent step, the trays 112 are assembled with the sections 113, to obtain a package 110, and subsequently to convey the package toward further working
20 stations.

The above described packaging method, which includes substantially the assembling of the trays 12, 112 to the sections 13, 113 of blank 11, 111, after the trays have been filled with corresponding discs 1, allows, first of
25 all, elimination of the problems deriving from undesired movements of the trays with respect to the blank after their gluing and before the gluing material dries.

In this way, a high operation regularity of the packaging machine is obtained, as well as simplification of the
30 structure with respect to similar machines.

- 11 -

This, in particular, occurs because the positioning of the discs with respect to the trays can be defined with extreme precision during their transfer toward the blank.

- 12 -

CLAIMS

1. A method for packaging disc-shaped digital record carriers in a corresponding folding package (10), said package (10) including a blank (11) and a tray (12) fastened to a corresponding section (13) of said blank (11,111), said method being characterized in that it includes a cyclical repetition of the following operation steps:
- 10- Feeding a tray (12) along a first path (A) of a line for packaging said discs (1), said tray having in its first surface (14) a housing (15) for receiving a disc (1);
- Feeding a disc (1) along a second path (B) of said packaging line, converging toward said first path (A) at a convergence point, and moving said disc (1) until it is aligned with the housing (15) of the tray (12);
- introducing said disc (1) in said housing (15);
- feeding said blank (11) along a third path (C) of said packaging line, said third path (C) intersecting said first path (A) at an assembling station of said package (10), downstream of the above mentioned convergence point between the first path (A) and the second path (B);
- 25- placing said tray (12) and said section (13) in mutual alignment, after introduction of the disc (1) into said tray (12);
- assembling, in said assembling station, said tray (12) to an inner surface (13a) of said section (13), with
- 30 interposition of a layer of gluing material, to fasten

- 13 -

said tray (12) to said section (13) and to obtain said package (10);

conveying said package (10) toward a station, where it is folded to the closed conformation.

5

2. A method as claimed in claim 1, characterized in that said gluing material is applied to a second surface (24) of each of said trays (12) facing said inner surface (13a) of the section (13), before introduction of the
10 disc (1) into the tray (12).

3. A method as claimed in claim 1, characterized in that said gluing material is applied to a second surface (24) of said tray (12) facing said inner surface (13a) of the
15 section (13), after the introduction of the disc (1) into the tray (12) and before assembling the tray to the blank.

4. A method as claimed in claim 1, characterized in that
20 said gluing material is applied to said inner surface (13a) of the section (13).

5. A method for packaging disc-shaped digital record carriers in a corresponding folding package (110), said
25 package (110) including a blank (111) and a predetermined number of trays (112), each of said tray being fastened to a corresponding section (113) of said blank (111), said method being characterized in that it includes a cyclical repetition of the following operation steps:

- 14 -

- feeding a predetermined number of trays (112), set side by side, along a first path (A) of a line for packaging said discs (1), each of said tray having a housing (115) in a first surface (114) for receiving a disc (1);
5
- feeding as many discs (1) as there are trays (112) the first path of the packaging line, along a second path (B) of said packaging line, converging toward said first path (A) at a convergence point, and placing each disc (1) in alignment with a housing (115) of a corresponding tray (112);
10
- introducing each of said discs (1) in a corresponding housing (115);
- feeding said blank (111) along a third path (C) of said packaging line, said third path (C) intersecting said first path (A) at an assembling station of said package (10), downstream of the above mentioned convergence point between the first path (A) and the second path (B);
15
- 20- setting each of said trays (112) in alignment with a corresponding section (113), after the introduction of the discs (1) into said trays (112);
- assembling, in said assembling station, each of said trays (112) to the inner surface (113a) of the corresponding sections (113), with interposition of a layer of gluing material, in order to fasten each tray (112) to a corresponding section (113) and to obtain said package (10);
25
- conveying said package (10) toward a station, where it is folded to the closed conformation.
30

- 15 -

6. A method as claimed in claim 5, characterized in that said gluing material is applied to a second surface (124) of each of said trays (112) facing a corresponding inner surface (113a) of the corresponding section (113), before
5 the introduction of the disc (1) into the corresponding tray (112).

7. A method as claimed in claim 5, characterized in that said gluing material is applied to a second surface (124)
10 of each of said trays (112) facing an inner surface (113a) of a corresponding section (113), after the introduction of the disc (1) into the corresponding tray (112) and before assembling the tray to the blank.

15 8. A method as claimed in claim 5, characterized in that said gluing material is applied to said inner surface (113a) of each section (113).

9. A method as claimed in claim 5, characterized in that,
20 after the discs (1) have been introduced into the corresponding trays (112), said trays (112) are spaced apart sidewise, in order to bring them to a position matching the correct distance on said blank (111), as a function of the selected modes of the subsequent folding
25 of the package (110).

THIS PAGE BLANK (USPTO)

1 / 3

FIG.1A




FIG.1B




FIG.1C






FIG.1D



THIS PAGE BLANK (USPTO)


2 / 3

FIG. 2



THIS PAGE BLANK (USPTO)

3 / 3



THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No
PC1, B2004/002000

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B65B25/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B65B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	US 2002/194821 A1 (GELARDI JOHN A) 26 December 2002 (2002-12-26) paragraph '0016! - paragraph '0021!; claims; figures	1,4,5,8 2,3,6,7, 9
X	US 5 788 114 A (PEREGO LUCIANO) 4 August 1998 (1998-08-04) column 16, line 37 - column 20, line 13; figures 10,13	1
A	US 4 551 966 A (WATANABE MAMORU ET AL) 12 November 1985 (1985-11-12) column 15, lines 53-62; figure 4	1,5
A	FR 2 049 092 A (MASSON SCOTT THRISSELL ENG LTD) 26 March 1971 (1971-03-26) page 9, line 31 - page 12, line 17; figures 1,2	1,5

-/-

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

5 October 2004

Date of mailing of the international search report

26/10/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Philippon, D

INTERNATIONAL SEARCH REPORT

Inter national Application No
PC 1, 1B2004/002000

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 2003, no. 05, 12 May 2003 (2003-05-12) & JP 2003 011916 A (HORON:KK; KANEMATSU SANGYO KIKAI KK; DIGITAL STREAMS INC; HOEI SANGYO), 15 January 2003 (2003-01-15) abstract -----	1,5
A	US 6 527 500 B1 (LESSARD GUY ET AL) 4 March 2003 (2003-03-04) column 4, line 33 - column 6, line 41; figures 1-12 -----	1,5
A	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 13, 30 November 1999 (1999-11-30) & JP 11 236001 A (TOSHIBA EMI LTD), 31 August 1999 (1999-08-31) abstract; figures -----	1,5
A	PATENT ABSTRACTS OF JAPAN vol. 2002, no. 06, 4 June 2002 (2002-06-04) & JP 2002 037212 A (KITANO ENGINEERING KK), 6 February 2002 (2002-02-06) abstract; figures -----	1,5

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB2004/002000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002194821 A1	26-12-2002	NONE	
US 5788114 A	04-08-1998	NONE	
US 4551966 A	12-11-1985	JP 1438613 C JP 57205851 A JP 62045625 B DE 3267556 D1 EP 0067073 A1 KR 8700686 B1	19-05-1988 17-12-1982 28-09-1987 02-01-1986 15-12-1982 06-04-1987
FR 2049092 A	26-03-1971	GB 1356923 A CA 929093 A1 FR 2049092 A5 GB 1316422 A JP 49009069 B US 3657858 A GB 1353152 A GB 1354291 A GB 1353003 A	19-06-1974 26-06-1973 26-03-1971 09-05-1973 01-03-1974 25-04-1972 15-05-1974 05-06-1974 15-05-1974
JP 2003011916 A	15-01-2003	NONE	
US 6527500 B1	04-03-2003	AU 2514700 A WO 0044622 A1	18-08-2000 03-08-2000
JP 11236001 A	31-08-1999	NONE	
JP 2002037212 A	06-02-2002	NONE	

THIS PAGE BLANK (USPTO)